

The i600 Dome

3 Axis / 360° / Hi-Res / Infrared



The i600 allows you to mount this Indoor Infrared Camera any way you need to, but still configure the picture upright and perfect.

The i600 Dome Cam is a 1/3", 600 Line - 0 Lux Camera with 24 Infrared LEDs that are controlled by a day/night sensor (they only come on at night).

12V DC

	Model #: i600
Optical Technology Base	1/3" Sony CCD High Resolution
Picture Elements (H x V in mm)	NTSC: 510(H) x 492(V) PAL: 500 (H) x 582(V)
Horizontal Resolution	600 Lines
Sync System	Internal
Vertical Frequency	NTSC: 59.94Hz PAL: 50Hz
Scanning System	2:1 Interlace
Mini Illumination	0 Lux (w/24 LEDs IR ON)
Synchronization	Internal
S/N Ratio	>48dB
Electronic Shutter	up to 1/100,000sec
White Balance	ATW
Lens	3.6mm lens
Gamma Correction	0.45
Auto Gain Control	Auto
Video Output	1Vp-p, 75 ohms
Operation Temperature	14°F to 122°F
Storage Temperature	-22°F to 140°F
Power Supply	DC12V
Power Consumption	400mA



201 N Elm St. • Kemp, Texas 75143

Toll Free: 866-301-CCTV

Phone: 903-498-3240

Fax: 903-498-8989

www.rugged-cctv.com